

ENERGY STAR Certified Homes, Version 3 / 3.1 (Rev. 08) 2017 Rater Quality Assurance Checklist

Home Address: City: State:	Zip Code:			
Action Items / Summary of QA	Yes		No	
If any Item marked "Must Correct," an action summary document shall be attached.				
Rater Design Review Checklist				
4. Review of HVAC Design Report			Not Visible	N/A
4.1 HVAC Design Report collected for records, with no Items left blank			-	
4.2 HVAC Design Report reviewed by Rater for the following parameters (HVAC Design Report Item # indicated in pare	nthesis):	:		
4.2.2 Number of occupants used in loads (3.4) is within ± 2 of the home to be certified			-	
4.2.3 Conditioned floor area used in loads (3.5) is between zero and 300 sq. ft. larger than the home to be certified			-	
4.2.4 Window area used in loads (3.6) is between zero and 60 sq. ft. larger than the home to be certified			-	
4.2.5 Predominant window SHGC (3.7) is within 0.1 of predominant value in the home to be certified			-	
Rater Field Checklist				
1. High-Performance Fenestration & Insulation				
1.2 Insulation meets or exceeds levels specified in Item 3.1 of the Rater Design Review Checklist, where Item 3.1 requires that specified ceiling, wall, floor, and slab insulation levels comply with one of the following options:				
3.1.1 Meets or exceeds 2009 IECC levels OR;	-	-	-	-
3.1.2 Achieves ≤ 133% of the total UA resulting from the U-factors in 2009 IECC Table 402.1.3, per guidance in Footnote 4d, AND specified home infiltration does not exceed the following:	_	_	-	_
3 ACH50 in CZs 1,2 2.5 ACH50 in CZs 3,4 2 ACH50 in CZs 5,6,7 1.5 ACH50 in CZ 8				
1.3 All insulation achieves RESNET-defined Grade I installation, or alternative per Footnote 4 of Rater Field Checklist				
2. Fully-Aligned Air Barriers				
2.3 At attic knee walls and skylight shaft walls, a complete air barrier provided that is fully aligned at exterior vertical surface of wall insulation in all climate zones; also at interior vertical surface of wall insulation in CZ 4-8				
3. Reduced Thermal Bridging				
3.1 For insulated ceilings with attic space above (i.e., non-cathedralized), Grade I insulation extends to the inside face of the exterior wall below and is ≥ R-21 in CZ 1-5; ≥ R-30 in CZ 6-8				
3.3 Insulation beneath attic platforms (e.g., HVAC platforms, walkways) ≥ R-21 in CZ 1-5; ≥ R-30 in CZ 6-8				
4. Air Sealing (Unless otherwise noted below, "sealed" indicates the use of caulk, foam, or equivalent material)				
4.1 Bathroom & kitchen exhaust fans that penetrate unconditioned space sealed, with blocking / flashing as needed. ¹				
4.2 Recessed lighting fixtures adjacent to unconditioned space ICAT labeled and gasketed. Also, if in insulated ceiling without attic above, exterior surface of fixture insulated to ≥ R-10 in CZ 4-8.				
 4.9 Doors adjacent to unconditioned space (e.g., attics, garages, basements) or ambient conditions made substaintially air-tight with weatherstripping or equivalent gasket 				
 4.10 Attic access panels, drop-down stairs, & whole-house fans equipped with durable ≥ R-10 cover that is gasketed (i.e., not caulked). Fan covers either installed on house side or mechanically operated. 				
6. Duct Quality Installation			1	
6.1 Ductwork installed without kinks, sharp bends, or excessive coiled flexible ductwork. ¹				
6.2 Bedrooms pressure-balanced using any combination of transfer grills, jump ducts, dedicated return ducts, and / or undercut doors to achieve Rater-measured pressure diff. ≤ 3 Pa with respect to main body of the house when all bedroom doors are closed & all air handlers are operating, or alternative per Footnote 34 of Rater Field Checklist				
6.3 All supply and return ducts in unconditioned space, including connections to trunk ducts, are insulated to $\geq R-6$.				
6.4 Rater-measured total duct leakage meets one of the following two options. See Footnote 37 of Rater Field Checklisi	for alter	native:		
6.4.1 <u>Rough-in</u> : The greater of ≤ 4 CFM25 per 100 sq. ft. of CFA or ≤ 40 CFM, with air handler & all ducts, building cavities used as ducts, & duct boots installed. In addition, <u>all</u> duct boots sealed to finished surface, Rater-verified at final.				
6.4.2 <u>Final</u> : The greater of ≤ 8 CFM25 per 100 sq. ft. of CFA or ≤ 80 CFM, with the air handler & all ducts, building cavities used as ducts, duct boots, & register grilles atop the finished surface (e.g., drywall, floor) installed.				
6.5 Rater-measured duct leakage to outdoors the greater of \leq 4 CFM25 per 100 sq. ft. of CFA or \leq 40 CFM25.				
7. Whole-House Mechanical Ventilation System				
7.7 Air inlet location (Complete if ventilation air inlet location was specified (2.12, 2.13); otherwise check "N/A"):				
7.7.1 Inlet pulls ventilation air directly from outdoors & not from attic, crawlspace, garage, or adjacent dwelling unit.				
7.7.2 Inlet is ≥ 10 ft. of stretched-string distance from known contamination sources (e.g., stack, vent, exhaust, vehicles) not exiting the roof, and ≥ 3 ft. from sources exiting the roof. ¹				



ENERGY STAR Certified Homes, Version 3 / 3.1 (Rev. 08) 2017 Rater Quality Assurance Checklist

8. Local Mechanical Exhaust			Passed	Must Correct	Not Visible	N/A
In each kitchen & b	pathroom, system is installed that exhaus	ts directly to outdoors & meets one of the following Rater-me	easured	airflow s	tandard	s:
Location	Continuous Rate	Intermittent Rate				
8.1 Kitchen ¹	≥ 5 ACH, based on kitchen volume	\geq 100 CFM and, if not integrated with range, also \geq 5 ACH based on kitchen volume				
8.2 Bathroom ¹	≥ 20 CFM	≥ 50 CFM				
9. Filtration						
9.1 At least one MERV 6 or higher filter installed in each ducted mechanical system in a location that facilitates access and regular service by the owner						
9.2 Filter access panel includes gasket or comparable sealing mechanism and fits snugly against the exposed edge of filter when closed to prevent bypass						
9.3 All return air and mechanically supplied outdoor air passes through filter prior to conditioning						
10. Combustion A	Appliances					
10.1 Furnaces, boilers, and water heaters located within the home's pressure boundary are mechanically drafted or direct-vented. See Footnote 56 of Rater Field Checklist for alternatives.						
10.3 If unvented combustion appliances other than cooking ranges or ovens are located inside the home's pressure boundary, the Rater has followed Section 805 of RESNET's Standards, encompassing ANSI/ACCA 12 QH- 2014, Appendix A, Section A3 (Carbon Monoxide Test), & verified the equipment meets the limits defined within.						

QA Designee:		Rater RTIN #:		
Status of home at time of inspection (e.g., under construction, occupied) :		Date of Inspection:		
Rater Company Name:				
Rater Name:	Rater RTIN #:		Rater Pre-Drywall Inspection Date:	
Rater Name:	Rater RTIN #:		Rater Final Inspection Date:	

Note: Additional checklist items may be inspected for quality insurance and included in the additional checklist items report.

Additional Checklist Items - Use this space to list additional Items reviewed (attach additional pages, if needed)						
Checklist Name	Item #	Notes	Passed	Must Correct	Not Visible	N/A

Footnotes

1. This represents a subset of the Revision 08 Item, rather than the complete Item.