

Amendment: Auxiliary Electric Energy of Ground Source Heat Pumps

Proponent:

RESNET Technical Committee

Applies to:

2006 Mortgage Industry National Home Energy Rating Systems Standards

Section 303.5 Operating Condition Assumptions Section 303.7 Minimum Rated Features

Proposed Amendment

Insert the following, and renumber subsequent sections as necessary: 303.5.1.7 For ground-loop and ground-water heat pumps, the Auxiliary Electric Consumption shall be determined as follows:

<u>GSHP Auxiliary Electric Consumption (kWh/yr) = $GSHP_{pump} + GSHP_{fan}$ </u>

Where:

<u>GSHP_{pump} in watts is the observed pump nameplate data (Volts *Amps) for all hours of heat</u> pump operation. Amps may be taken from nameplate as Run Load Amps (RLA) or Full Load Amps (FLA). Alternatively, pumping energy that is measured on-site with a watt-hour meter, or using measured V*A may be substituted. Such measured pumping energy may be further adjusted for on-site measured duty cycle during heat pump operation, when pumping is intermittent during continuous heat pump operation.

<u>GSHP_{fan}: If ducts are attached to the system to deriver heating or cooling, the external fan</u> energy in watts, <u>GSHP_{fan} = (air flow in CFM * 0.5 CFM per watt)</u>, shall be added for all hours of heat pump operation. The air flow in CFM shall be (360 * rated cooling btu/h / 12,000), where 360 is the air flow in CFM per ton (12 kbtu/h) of capacity..

Table 303/7.1(1) Minimum Rated Features

12. Heating Equipment	Equipment type, location, efficiency (AFUE, HSPF), auxiliary electric (Eae): power consumption of ground fluid circulating pump(s) for ground-loop and
	ground-water heat pumps.

Background/Rationale:

Since the adoption of the 2006 RESNET standards, auxiliary electric energy has been a minimum rated feature for fossil-fuel heating equipment. For comparable treatment, auxiliary electric energy that is required for the operation of ground-source heat pumps should be included as a minimum rated feature. This amendment provides guidance for treatment of auxiliary electric energy in the reference and rated homes when a ground-source heat pump is present. Furthermore, the current ARI/ISO standard 13256 that is used to test these devices specifically excludes any fan power required to move air through ducts (rated at 0 external static pressure).